

Pillowcase Pattern

Fabric needed: $\frac{3}{4}$ yard main print
 $\frac{1}{8}$ yard for trim
 $\frac{1}{3}$ yard for band

Assembly Instructions:

1. Trim the $\frac{1}{8}$ yard of fabric to the desired width— $2\frac{1}{2}$ inches works well.
2. Fold the trim in half lengthwise, wrong sides together. Press.
3. Lay the main fabric right side up, raw edge at top (see diagram), selvages down the sides
4. Pin the trim piece to the right side of the main fabric, matching raw edges.
5. From the opposite end (bottom of the diagram), roll the edges of the main fabric up to the pinned area rolling it underneath the band fabric.
7. Take the long raw edge of the band fabric and fold it around the rolled up main fabric to the back side. The right side the band fabric will now match the wrong side of the main fabric. Match the raw edges and pin in place.
8. Sew across the width over the pinned seam. This will form a tube.
9. Reach in the tube and pull out the main fabric.
10. Press well.
11. Sew the side seam with a French seam or serge.
12. Sew the end with a French seam or serge.

Directions for French seam:

1. Match raw edges with wrong sides together.
2. Sew a $\frac{1}{8}$ -inch seam. It is important to sew a small seam.
3. Press well.
4. Fold along seam so that right sides are together, with raw edges inside.
5. Sew again, this time with a $\frac{1}{4}$ - to $\frac{3}{8}$ -inch seam.

Trim →

